


EL2848

Temperature Rating: Cone 10


Volume: 20 Cubic Feet

Inside Dim: 31" W x 25" D x 48" H

Hearth Size: 28" x 22"



31" W x 25" D x 48" H



72 in

78.8 in



Commercial-grade front-loading kilns for production. Includes adjustable door with plug seal and fiberglass gasket, door elements, heavy-gauge welded case, 4.5" K25 arched brick top, door switch, and industrial control panel with branch fusing.

- **Genesis Touch Screen Control** • with Kiln Aid app
- **Dynamic Zone Control** • for even firing
- **Hard Ceramic Element Channels** • protect your elements and kiln
- **Door Elements**
- **Cone 10** (2350°F • 1290°C)
- **Type K Thermocouples (3)** • with protection tubes
- **3" K23 Brick** • 2" of backup insulation and 4.5" K25 arched top
- **Front Loading**
- **Solid, Straight-View Peephole Plugs**
- **Welded, Powder-Coated Case/Frame**
- **Industrial Control Panel** • 480v optional
- **Two-Year Limited Commercial Warranty**
- **MET-us listed to UL499 Standards**
- **See hotkilns.com/EL2848 for all features and options**

GENERAL DIMENSIONS



TRUST YOUR KILN
hotkilns.com

Manufactured in Swedesboro, NJ
800-750-8350 • sales@hotkilns.com

Bulletin No: BL-EL2848 REV: 0

Page 1




Electrical Specifications for EL2848

USA

Model Number	Part Number	Volt/ Phase	Watts	Amps	Wire Size	Fuse Size
EL2848-240	K-B-2848/31	240/1P	27,000	112.5	3/0	150 Amps
EL2848-240-3P	K-B-2848/32	240/3P	27,000	65.0	2 ga	90 Amps
EL2848-208	K-B-2848/21	208/1P	27,000	129.8	4/0	175 Amps
EL2848-208-3P	K-B-2848/22	208/3P	27,000	74.9	1 ga	100 Amps
EL2848-480-3P	K-B-2848/62	480/3P	27,000	32.5	6 ga	50 Amps

WORLD

Model Number	Part Number	Volt/ Phase	Watts	Amps	Wire Size	Fuse Size
EL2848-220	K-B-2848/41	220/1P	27,000	122.7	4/0	175 Amps
EL2848-380-3PY	K-B-2848/52	380/3PY	27,000	40.9	6 ga	60 Amps
EL2848-400-3PY	K-B-2848/82	400/3PY	27,000	39.1	2 ga	90 Amps
EL2848-415-3PY	K-B-2848/72	415/3PY	27,000	37.5	2 ga	90 Amps



Control: Full digital touchscreen Genesis control with easy-to-use interface, WiFi enabled app, and simple programs for firing ceramics or glass.

MET UL499 Listing: All models are MET-us listed to UL499 standards. They are not listed to CSA standards.

Power connection: All models are a direct connection to a terminal block in the control panel.

Packaging: Fully crated with shock absorbing pallets. Requires forklift to unload.

EASY-LOAD CHECKLIST




Scan OR Visit:
hotkilns.com/support/pdfs/easy-load-installation-checklist

FURNITURE KIT FOR EL2848H

Part Number: H-B-2848/00

Includes: Twelve 14" x 24" Rectangular Shelves (3/4" thick), Twelve Each 1/2", 1", 2", 4", 6", and 8" Square Posts, Heat Resistant Gloves.



TRUST YOUR KILN
hotkilns.com

Manufactured in Swedesboro, NJ
 800-750-8350 • sales@hotkilns.com

Bulletin No: BL-EL2848 REV: 0

Page 2

