

L&L KILN MFG

DIMENSION SPECIFICATIONS

FOR DAVINCI KILNS

DAVINCI KILNS (Both manual and automatic) ENGLISH DIMENSIONS

MODEL	ENGLISH DIMENSIONS (INCHES)																		
	KILN DIMENSIONS AND INTERIOR VOLUME										SHIPPING DIMENSIONS						SHIPPING WEIGHT		
	INSIDE DIMENSIONS			CUBIC FEET	OUTSIDE DIMENSIONS			SPACE NEEDED FOR KILN			CRATE ONE			CRATE TWO (HINGE)			No shelf kit LBS	With Shelf Kit LBS	Shelf Kit LBS
	Width	Depth	Height		Width	Depth	Height	Width	Depth	Height	Width	Height	Depth	Width	Height	Depth			
X1818	17.5	17.5	18	3.4	34	32	32	49	49	78	44	45	44	36	74	36	675	716	41
X1827	17.5	17.5	27	5.1	34	32	41	49	49	87	44	54	44	36	84	36	750	803	53
XB2318	22.0	22.0	18	5.0	40	42	32	54	54	78	54	45	48	44	74	44	800	846	46
X2327	22.0	22.0	27	8.1	40	42	41	54	54	87	54	54	48	44	84	44	900	964	64
X2336	22.0	22.0	36	10.8	40	42	50	54	54	96	54	63	48	44	84	44	975	1067	92
X2345	22.0	22.0	45	13.5	40	42	59	54	54	102	54	72	48	44	84	44	1075	1185	110
XB2818	26.5	26.5	18	7.8	45	43	32	59	59	78	54	45	48	44	74	44	975	1045	70
X2827	26.5	26.5	27	11.7	45	43	41	59	59	87	54	54	48	44	84	44	1085	1185	100
X2836	26.5	26.5	36	15.6	45	43	50	59	59	96	54	63	48	44	84	44	1185	1325	140
X2845	26.5	26.5	45	19.5	45	43	59	59	59	102	54	72	48	44	84	44	1300	1470	170
XB3218	30.5	30.5	18	10.0	49	49	32	64	64	78	54	45	48	44	74	44	1180	1282	102
X3227	30.5	30.5	27	15.0	49	49	41	64	64	87	54	54	48	44	84	44	1300	1448	148
X3236	30.5	30.5	36	20.0	49	49	50	64	64	96	54	63	48	44	84	44	1435	1639	204
X3245	30.5	30.5	45	25.0	49	49	59	64	64	102	54	72	48	44	84	44	1575	1825	250
TB2318	35.3	26.5	18	9.7	54	43	32	60	69	78	62	45	48	54	74	48	1250	1344	94
T2327	35.3	26.5	27	14.6	54	43	41	60	69	87	62	54	48	54	84	48	1385	1521	136
T2336	35.3	26.5	36	19.4	54	43	50	60	69	96	62	63	48	54	84	48	1515	1703	188
T2345	35.3	26.5	45	24.3	54	43	59	60	69	102	62	72	48	54	84	48	1650	1880	230
TB3418	43.5	30.5	18	13.8	62	49	32	66	76	78	62	45	48	62	74	48	1415	1573	158
T3427	43.5	30.5	27	20.7	62	49	41	66	76	87	62	54	48	62	84	48	1575	1802	227
T3436	43.5	30.5	36	27.6	62	49	50	66	76	96	62	63	48	62	84	48	1825	2121	296
T3445	43.5	30.5	45	34.5	62	49	59	66	76	102	62	72.0	48	62	84	48	2025	2400	375

NOTE: For 480 Volt kilns there is a third skid that holds the industrial control panel, typical size is 44" wide by 44" deep by 48" high.

NOTE: For the "Bell-Lift" option there will be a third skid the size of width & depth of skid number one with the height of skid number two. Add 900 pounds to shipping weight.

L&L KILN MFG

DIMENSION SPECIFICATIONS

FOR DAVINCI KILNS

DAVINCI KILNS (Both manual and automatic) METRIC DIMENSIONS

MODEL	METRIC DIMENSIONS (CENTIMETERS)																		
	KILN DIMENSIONS AND INTERIOR VOLUME										SHIPPING DIMENSIONS						SHIPPING WEIGHT		
	INSIDE DIMENSIONS			CUBIC Meter	OUTSIDE DIMENSIONS			SPACE NEEDED FOR KILN			CRATE ONE			CRATE TWO (HINGE)			No shelf kit	With Shelf Kit	Shelf Kit
	Width	Depth	Height		Width	Depth	Height	Width	Depth	Height	Width	Height	Depth	Width	Height	Depth	KG	KG	KG
X1818	44.5	44.5	45.7	0.10	86	81	81	124	124	198	112	114	112	91	188	91	306	325	19
X1827	44.5	44.5	68.6	0.14	86	81	104	124	124	221	112	137	112	91	213	91	340	364	24
XB2318	55.9	55.9	45.7	0.14	100	107	81	137	137	198	137	114	122	112	188	112	363	384	21
X2327	55.9	55.9	68.6	0.23	100	107	104	137	137	221	137	137	122	112	213	112	408	437	29
X2336	55.9	55.9	91.4	0.31	100	107	127	137	137	244	137	160	122	112	213	112	442	484	42
X2345	55.9	55.9	114.3	0.38	100	107	150	137	137	259	137	183	122	112	213	112	488	538	50
XB2818	67.3	67.3	45.7	0.22	114	109	81	150	150	198	137	114	122	112	188	112	442	474	32
X2827	67.3	67.3	68.6	0.33	114	109	104	150	150	221	137	137	122	112	213	112	492	538	45
X2836	67.3	67.3	91.4	0.44	114	109	127	150	150	244	137	160	122	112	213	112	538	601	64
X2845	67.3	67.3	114.3	0.55	114	109	150	150	150	259	137	183	122	112	213	112	590	667	77
XB3218	77.5	77.5	45.7	0.28	124	124	81	163	163	198	137	114	122	112	188	112	535	582	46
X3227	77.5	77.5	68.6	0.42	124	124	104	163	163	221	137	137	122	112	213	112	590	657	67
X3236	77.5	77.5	91.4	0.57	124	124	127	163	163	244	137	160	122	112	213	112	651	743	93
X3245	77.5	77.5	114.3	0.71	124	124	150	163	163	259	137	183	122	112	213	112	714	828	113
TB2318	89.5	67.3	45.7	0.27	136	109	81	152	175	198	157	114	122	137	188	122	567	610	43
T2327	89.5	67.3	68.6	0.41	136	109	104	152	175	221	157	137	122	137	213	122	628	690	62
T2336	89.5	67.3	91.4	0.55	136	109	127	152	175	244	157	160	122	137	213	122	687	772	85
T2345	89.5	67.3	114.3	0.69	136	109	150	152	175	259	157	183	122	137	213	122	748	853	104
TB3418	110.5	77.5	45.7	0.39	157	124	81	168	193	198	157	114	122	157	188	122	642	714	72
T3427	110.5	77.5	68.6	0.59	157	124	104	168	193	221	157	137	122	157	213	122	714	817	103
T3436	110.5	77.5	91.4	0.78	157	124	127	168	193	244	157	160	122	157	213	122	828	962	134
T3445	110.5	77.5	114.3	0.98	157	124	150	168	193	259	157	183	122	157	213	122	919	1089	170

NOTE: For 480 Volt kilns there is a third skid that holds the industrial control panel, typical size is 112 CM wide by 112 CM deep by 122 CM high.

NOTE: For the "Bell-Lift" option there will be a third skid the size of width & depth of skid number one with the height of skid number two. Add 45 KG to shipping weight.

NOTE: Crate sizes and weights are approximate and can vary.