1. WALL/KILN SPACING: 12" [30.5cm] SPACING BETWEEN SIDES OF KILN AND WALLS OR OTHER OBJECTS. 18" [45.7cm] IS RECOMMENDED. LEAVE AT LEAST 18" [45.7cm] BETWEEN TWO KILNS.

2. AMBIENT VENTILATION: SEE CHART TO RIGHT FOR RATINGS. TO CALCULATE REQUIREMENTS, SEE hotkilns.com/calculate-kiln-room-ventilation.

NEW

- 3. KILN VENTILATION: L&L VENT-SURE KILN VENT RECOMMENDED FOR SAFETY AND LONGER ELEMENT LIFE. OPTIONAL CONTROL ALLOWS VENT TO BE TURNED ON AND OFF WITH CONTROL.
- **OTHER INFO: REFER TO INSTALLATION INSTRUCTIONS AND** 4 CAUTIONS INSTRUCTIONS FOR OTHER REQUIREMENTS AND SAFETY INFORMATION. REFER TO WIRING DIAGRAM FOR ELECTRICAL HOOKUP INFORMATION.

BTUS/ KILOJOULES PER HOUR NEEDED TO BE VENTED WITH AMBIENT ROOM VENTILATION (THIS IS IN ADDITION TO KILN VENTING):

- MAX LOAD WEIGHT: SEE hotkilns.com/load-weight. 5.
- 6. WEIGHT OF KILN: 810 LBS, 367 KG

BTUS AT TEMP C **KILOJOULES** AT TEMP F 1800F 21945 980C 23153 LID NOT SHOWN VIEW SCALE - 1:18 1095C 27066 2000F 25654 IN THIS VIEW 2232F 30290 1222C 31958 2350F 32783 1285C 34588 12.0in [30.5cm] LEAVE AT LEAST THIS MODEL IS 30" FREE SPACE FROM A KILN DIRECT WIRED. SURFACE FOR THERE IS NO USER TO LOAD KILN POWER CORD. 89.5in [227.3cm] 12.0in [30.5cm] LEAVE 24" FREE SPACE IN FRONT OF CONTROLLER FOR OPERATION 23" [58.4cm] X 11.5" [29.2cm] AND MAINTENANCE RECTANGULAR KILN FURNITURE (OPTIONAL) 75.6in [192cm] 505 SHARPTOWN RD REV DRAWING NO. SHEET OF MADE FROM DRAWN BY DATE SCALE TITLE 04/15/20 1/3 300-000-30-4 SJL 1:22 X2836-D (3" BRICK) DAVINCI GENERAL DIMENSIONS (856) 294-0077 0 5 3 ۸ 2



