Easy-Fire Kilns



This is the classic L&L pottery kiln used by most of our customers. They include all the signature L&L features.

GENERAL DIMENSIONS



Scan OR Visit: hotkilns.com /e23S-3-GD



- Genesis Touch Screen Control with Kiln Aid app
- Dynamic Zone Control for even firing
- Hard Ceramic Element Channels protect your elements and kiln
- Type K Thermocouples (2) with protection tubes
- Top Loading
- Solid, Straight-View Peephole Plugs
- Full-Support Stand rolling option available
- Easy-Access Control Panel with Easy-View tilted display
- Three-Year Limited Warranty

Page 1

- c-ETL-us listed to UL499 Standards
- See hotkilns.com/e23s-3 for all features and options

TRUST YOUR KILN hotkilns.com

Manufactured in Swedesboro, NJ 800-750-8350 • sales@hotkilns.com Bulletin No: BL-e23S-3 REV: A



Model Numbers	Part Number	Volt/	Watts	Amps	Wire	Fuse	Power
	for 3" Brick	Phase			Size	Size	Connection
e23S-3-240	K-E-23S3/31	240/1P	9,460	39.4	6 ga	50 Amps	6-50 Cordset
e23S-3-240-3P	K-E-23S3/32	240/3P	9,460	34.1	6 ga	50 Amps	15-50 Cordset
e23S-3-208	K-E-23S3/21	208/1P	8,320	40.0	6 ga	50 Amps	6-50 Cordset
e23S-3-208-3P	K-E-23S3/22	208/3P	8,320	34.6	6 ga	50 Amps	15-50 Cordset
e23S-3-220	K-E-23S3/41	220/1P	8,660	39.4	6 ga	50 Amps	Direct Wire
e23S-3-380-3PY	K-E-23S3/52	380/3PY	8,660	19.7	12 ga	25 Amps	Direct Wire

Electrical Specifications for e23S-3 SERIES

USA

Start	IDLE				
Edit	Ceramic Glaze Cone 022 Fast				
Load	Current Temperature Fire Time				
Menu	Seg1 of 3 -°F				

Control: Full digital touchscreen Genesis control with easy-to-use interface, WiFi enabled app, and simple programs for firing ceramics.

UL Listing: All models are c-ETL-us listed to UL499 standard.

Cone Rating: All e23 models are rated to Cone 10.

Wiring Diagrams: See **the Electrical Tab** for each kiln model to get the wiring diagram for each voltage.

Power connection: A six foot cord with a 50 amp NEMA 6-50 for single phase units or a 15-50 plug for 3 phase units is included. (No neutral is necessary). World voltage kilns do not include a cord - they are direct wired. All kilns may be direct wired.

Elements: All elements are of equal resistance value. S models have four elements. Quad elements are the same resistance and quantity but longer and thicker.

Other voltages for any country in the world are available. Examples are 200V/3 Phase Delta, 220V/3 Phase Delta, 415V/3 Phase Wye and 400V/3 Phase Wye. CE Listing available in some countries. See 380 Volt diagrams for electrical specifications for 400V/3 Phase Wye and 415V/3 Phase Wye.

Moving and installation: The kiln comes assembled but can be quickly disassembled and reassembled to move through any door or up stairs. It comes packed in a skidded carton with secure foam-in-place packaging.

Shipping Dimensions: See website for shipping dimensions with various combinations of options.



FURNITURE KIT FOR e23S-3

Part Number: H-E-K23S/30

Includes: Six 20" (50.8 cm) half shelves, one post kit with six each 1/2", 1", 2", 4", 6", and 8" square posts, and one pair heat resistant gloves.

TRUST YOUR KILN hotkilns.com

Manufactured in Swedesboro, NJ 800-750-8350 • sales@hotkilns.com Bulletin No: BL-e23S-3 REV: A

