


Panel



Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

Wiring Information

Power	10AWG / 150°C / 600V
Control	16AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Model: e23S-380-3PY

Voltage	380 / 3-Y / 50-60
Watts	8,660
Full Load Amps	L1 19.7 L2 19.7 L3 0
Power Supply	Fuse 25A Wire 12AWG
Standard Elements: E-E-23SL/41	
Quad Elements: E-E-23SU/41	
Quantity: 4	Ohms: 21.5

Model: e23S-400-3PY

Voltage	400 / 3-Y / 50-60
Watts	9,834
Full Load Amps	L1 21.4 L2 21.4 L3 0
Power Supply	Fuse 30A Wire 10AWG
Standard Elements: E-E-23SL/41	
Quad Elements: E-E-23SU/41	
Quantity: 4	Ohms: 21.5

Model: e23S-415-3PY

Voltage	415 / 3-Y / 50-60
Watts	9,460
Full Load Amps	L1 19.7 L2 19.7 L3 0
Power Supply	Fuse 25A Wire 12AWG
Standard Elements: E-E-23SL/31	
Quad Elements: E-E-23SU/31	
Quantity: 4	Ohms: 23.4

E23S Easy-Fire 3 Phase Wye 380V, 400V, 415V



505 Sharptown Road
Swedesboro NJ 08085
service@hotkilns.com
(856)-294-0077

Drawn by: JS

Rev. Date Description C0021