


Wiring Information	
Power	10AWG / 150°C / 600V
Control	16-22AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Model: DLH11-DX-208			
Voltage	208 / 1 / 50-60		
Watts	2,800		
Full Load Amps	L1	L2	L3
	13.5	13.5	
Power Supply	Fuse	Wire	
	20A	14AWG	
Elements E-D-DHLL/20	QTY	OHMS	
	3	5.0	

Model: DLH11-DX-240			
Voltage	240 / 1 / 50-60		
Watts	2,800		
Full Load Amps	L1	L2	L3
	11.7	11.7	
Power Supply	Fuse	Wire	
	15A	14AWG	
Elements E-D-DHLL/30	QTY	OHMS	
	3	6.6	

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

DLH11-DX 1 Phase 208V, 240V (C0042)				
A	05/06/2026		AF	Drawn by: AF
Rev.	Date	Description	Approved by	Dwg. No. C0042