



Note: Dynatrol Control Board (P/N: N-G-D300/00) can be used as a substitute control

Wiring Information			
Power	10AWG / 150°C / 600V		
Control	16-22AWG / 105°C / 600V		
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.			
Model: e14S-208			
Voltage	208 / 1 / 50-60		
Watts	3,840		
Full Load Amps	L1	L2	L3
	18.5	18.5	
Power Supply	Fuse	Wire	
	25A	12AWG	
Elements E-F-14SL/21	QTY	OHMS	
	4	10.8	

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the KW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

E14S Easy-Fire 1 Phase 208V (C0001)					
				505 Sharptown Road Swedesboro NJ 08085 service@hotkilns.com	
				(856)-294-0077	
A	05/12/2026		AF	Drawn by: AF	
Rev.	Date	Description	Approved by	Dwg. No. C0001	