



Note: Dynatrol Control Board (P/N: N-G-D300/00) can be used as a substitute control

Wiring Information	
Power	10AWG / 150°C / 600V
Control	16-22AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Model: e14S-240			
Voltage	240 / 1 / 50-60		
Watts	3,840		
Full Load Amps	L1	L2	L3
	16.0	16.0	
Power Supply	Fuse	Wire	
	20A	14AWG	
Elements	QTY	OHMS	
	E-F-1418/31	4	14.4

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

E14S Easy-Fire 1 Phase 240V (C0002)					
				505 Sharptown Road Swedesboro NJ 08085 service@hotkilns.com (856)-294-0077	
A	05/12/2026		AF	Drawn by: AF	
Rev.	Date	Description	Approved by	Dwg. No. C0002	