



Note: Dynatrol Control Board (P/N: N-G-D300/00) can be used as a substitute control

Wiring Information	
Power	10AWG / 150°C / 600V
Control	18-22AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

Model: e18T-208		
Voltage	208 / 1 / 50-60	
Watts	8,400	
Full Load Amps	L1	L3
	40.4	40.4
Power Supply	Fuse	Wire
	60A	6AWG
Elements	QTY	OHMS
	E-E-18TL/21	6 7.44

Model: e18T-240		
Voltage	240 / 1 / 50-60	
Watts	8,400	
Full Load Amps	L1	L3
	35.0	35.0
Power Supply	Fuse	Wire
	50A	8AWG
Elements	QTY	OHMS
	E-E-18TL/31	6 9.90

E18T Easy-Fire 1 Phase 208V, 240V (C0012)				
A	05/12/2026		AF	Drawn by: AF
Rev.	Date	Description	Approved by	Dwg. No. C0012