



Wiring Information	
Power	10AWG / 150°C / 600V
Control	16-22AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Model: e23M-208	
Voltage	208 / 1 / 50-60
Watts	9,985
Full Load Amps	L1 48.0 L2 48.0 L3 48.0
Power Supply	Fuse 60A Wire 6AWG
Standard Elements:	E-E-23ML/21
Quad Elements:	E-E-23MQ/21
Quantity:	5
Ohms:	20.9

Model: e23M-240	
Voltage	240 / 1 / 50-60
Watts	11,520
Full Load Amps	L1 48.0 L2 48.0 L3 48.0
Power Supply	Fuse 60A Wire 6AWG
Standard Elements:	E-E-23ML/31
Quad Elements:	E-E-23MQ/31
Quantity:	5
Ohms:	24.1

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

E23M Easy-Fire 1 Phase 208V, 240V (C0016)				
A	05/11/2026		AF	Drawn by: AF
Rev.	Date	Description	Approved by	Dwg. No. C0016