



Wiring Information	
Power	10AWG / 150°C / 600V
Control	16-22AWG / 105°C / 600V
Power Supply Wire Gauge assumes 75°C Copper Wire. See hotkilns.com/wire-size.	

Model: e23T-208				
Voltage	208 / 1 / 50-60			
Watts	9,980			
Full Load Amps	L1	L2	L3	
	48.0	48.0		
Power Supply	Fuse	Wire		
	60A	6AWG		
Standard Elements: E-E-23TL/21				
Quad Elements: E-E-23TU/21				
Quantity: 6	Ohms: 25.0			

Model: e23T-240				
Voltage	240 / 1 / 50-60			
Watts	11,520			
Full Load Amps	L1	L2	L3	
	48.0	48.0		
Power Supply	Fuse	Wire		
	60A	6AWG		
Standard Elements: E-E-23TL/31				
Quad Elements: E-E-23TU/31				
Quantity: 6	Ohms: 28.9			

Industrial & commercial applications may require the installation of a LOCKOUT/TAGOUT device to prevent the kiln from operating during maintenance.

This kiln is recommended to be wired & connected to an approved U. L. & NEC configured receptacle controlled with a disconnect switch and properly fused according to the kW load specification listed on the kiln nameplate. L&L Kiln Mfg., Inc., also recommends fuses rather than circuit breakers to prevent nuisance tripping.

E23T Easy-Fire 1 Phase 208V, 240V (C0024)				
A	05/08/2026		AF	Drawn by: AF
Rev.	Date	Description	Approved by	Dwg. No. C0024